



STANDARD	NIJ 0101.06
NIJ MODEL	BA-3A00S-SX03F
SERIES	EX02
THREAT LEVEL	IIIA
GENDER	Female
AREAL DENSITY	0.88 psf
THINNESS	0.20"
SIZE RANGE	C1-C5
COMPOSITION	SAATI, Gold Shield®, and Dyneema®
PANEL COVER	Dual Covered, 2 Ply, 70 Denier Textured Nylon Ripstop with TPU Lamination System
WARRANTY	5 Years



### BALLISTIC PERFORMANCE AT CERTIFICATION

.357 Sig New V50	1778 fps	.44 Mag New V50	1680 fps
.357 Sig Conditioned V50	1818 fps	.44 Mag Conditioned V50	1621 fps
.357 Sig BFS	29.9 mm	.44 Mag BFS	37.6 mm
.357 Sig New RPI	2021	.44 Mag New RPI	1909
.357 Sig Conditioned RPI	2066	.44 Mag Conditioned RPI	1842

### SPECIAL THREAT TESTING

Winchester 9mm 127 gr. SXT +P+ RA9TA | Federal 9mm 100 gr. Frangible | Speer .357 SIG 125 gr. GDHP  
 Winchester .40 S&W 165 gr. SXT | Romanian 7.62x25mm 85 gr. Tokarev | FN 5.7x28mm 40 gr. Blue Tip SS197SR  
 FN 5.7x28mm 27 gr. JHP SS195 LF

Special threat testing conducted at NIJ certified independent laboratory